



CamLite™ Model 1000 Specifications:

CamLite™ Model 1000	Power Operating time (camera only) Operating time (using flashlight) Lamp life Transmission distance ¹	NiMH rechargeable battery pack Approx. 8 hours Approx. 3 hours Approx. 50 hours Approx. 1000 feet line of sight
Indicators	Power on for camera, laser pointer and microphone Low battery	
Camera	Actual number of pixels Frames per second Minimum illumination Resolution - horizontal Resolution - vertical Power supply range Temperature range (operating) Video format	512H x 492V 30 6 lx Min 330 lines (center area) Min 350 lines (center area) DC 4.8 ~ 5.5 V 14°F ~ +122°F NTSC
Receiver box	Internal power External power Audio output Video output Antenna connection	NiMH rechargeable battery pack 12V - 5.00A 60W power supply RCA jack BNC jack N connector
Recharging times	CamLite™ Model 1000 battery pack Receiver box batteries Optional SONY GV -D800 battery Using receiver box recharger Using SONY supplied recharger	Approx. 2 hours Approx. 2 hours Approx. ___ hours Approx. ___ hours
Dimensions	CamLite™ Model 1000	13 5/8" length x 2 3/4" diameter
Weight	CamLite™ flashlight	1.2 lbs

1. Transmission distance can be adversely affected by obstacles, battery power, position of CamLite™ Model 1000 and other factors.